








Photometric data:



OLD-OBZDX



ORION INTERNATIONAL Performance parameter	
LED Light Source: Cree, Lumileds, Osram, Epistar	Effects: single color, full color, gradient, chasing, flowing
Color Temperature: single color, RGB, RGBW, RGBA, RGB+W	Protection Grade: IP65
LED CRI: ≥ 80 R9>0	Electrical Safety Level: Class I / III
Lifespan: ≥ 50000h	Voltage: AC220V 50/60Hz DC24V
Beam Angle: 8~110° 10x30° 10x60° 25x45° (optional)	Current: constant current drive
Rotation Angle: unadjustable	Working Temperature: -35°C ~ +45°C
Control Mode: ON/OFF, DMX512	Mounting Bracket: customizable

ORION INTERNATIONAL Optional accessories




Ground Stake

ORION INTERNATIONAL Features

- Suitable for cylindrical tree lighting
- Thick, fashionable and compact appearance; die-cast aluminum lamp body of high density material; anti-UV outdoor spraying treatment.
- Full sealed and waterproof
- 4mm toughened glass

ORION INTERNATIONAL Product Size



Model	Dia. () Ø	Height (H)
4 Modules	281mm	163mm
5 Modules	290mm	
6 Modules	301mm	
7 Modules	325mm	
8 Modules	337mm	



ORION INTERNATIONAL Product number

Model	Power	Input Voltage	LED Quantity	Single LED	Color
OLD-OBZDX-D	6~15W	AC220V/DC24V	6	1~3W	Single color
OLD-OBZDX-R	6~24W	DC24V	6	1~4W	Full Color